

**Panasonic KV-S1025C Duplex Sheetfed Scanner Specifications**

Manufacturer		Panasonic
Manufacturer Part #		KV-S1025C
Scanner	Type	Sheetfed Scanner
	Scanning Element	3 Line Color CCD
	Light Source	White fluorescent lamp
	Operating Mode	Simplex, Duplex
	Resolution	600 dpi
	Max. Scan Area	8.6" x 101.6" ADF
	Scanning Speed	Binary 200 dpi: 26 ppm, 52 ipm duplex Color 200 dpi: 26 ppm, 52 ipm duplex
	Color Depth Grayscale Depth	24-bit 8-bit
Connectivity	Hardware	USB 2.0
	Software	ISIS (AIIM MS161S standard)/TWAIN
Paper Handling	Document Feeding Mode	Manual, Automatic
	ADF Capacity	50 Sheet
	Document Size	Minimum: 1.9" x 2.8" Maximum: 8.6" x 101.6"
	Document Weight	Single: 11 - 55 lb. bond (40 - 209 g/m2), Up to 115 lb. index Continuous: 11 - 55 lb. bond (40 - 209 g/m2), Up to 115 lb. index
Software		RTIV, Quick Scan Pro DEMO, ABBYY FineReader 7 Professional
Additional Information	Additional Hardware	Feed Tray, Mixed Batch Card Guide (pre-installed), AC Adapter, Power Cord, USB Cable
Power Requirements	Voltage	AC 100 - 120 V, 50/60 Hz
	Consumption	Scanning Mode 32W
		Idle Mode 22W Sleep Mode Less Than 12W
Operating Conditions	Temperature	59 - 86 Degrees F
	Humidity	30% - 80% RH
Dimensions (Without Feed Tray) (W x H x D)	Unit	Without Stand: 12.3" x 7.6" x 6.7"
		With Stand: 12.5" x 7.8" x 8.6"
Weight	Unit	9.3 lbs. with stand
System Requirements	PC	IBM PC/AT or compatible PC
		CD-ROM Drive
		Pentium III 1 GHz or higher
		USB 2.0 Interface
		Windows 2000 or XP
		256 MB RAM Minimum 200 MB free space (except for data file)