

Panasonic KV-S1020C Sheetfed Scanner Specifications

Manufacturer Manufacturer Part #		Panasonic KV-S1020C
Scanner	Type Scanning Element Light Source Operating Mode Resolution Max. Scan Area Scanning Speed Color Depth Grayscale Depth	Sheetfed Scanner 3 Line Color CCD White fluorescent lamp Simplex 600 dpi 8.6" x 101.6" ADF Binary 200 dpi: 26 ppm Color 200 dpi: 26 ppm 24-bit 8-bit
Connectivity	Hardware Software	USB 2.0 ISIS (AIIM MS161S standard)/TWAIN
Paper Handling	Document Feeding Mode ADF Capacity Document Size Document Weight	Manual, Automatic 50 Sheet Minimum: 1.9" x 2.8" Maximum: 8.6" x 101.6" Single: 11 - 55 lb. bond (40 - 209 g/m2), Up to 115 lb. index Continuous: 11 - 55 lb. bond (40 - 209 g/m2), Up to 115 lb. index
Software		RTIV, Quick Scan Pro DEMO, ABBYY FineReader 7 Professional
Additional Information	Additional Hardware	Feed Tray, Mixed Batch Card Guide (pre-installed), AC Adapter, Power Cord, USB Cable
Power Requirements	Voltage Consumption	AC 100 - 120 V, 50/60 Hz Scanning Mode 24W Idle Mode 14W Sleep Mode Less Than 12W
Operating Conditions	Temperature Humidity	59 - 86 Degrees F 30% - 80% RH
Dimensions (Without Feed Tray) (W x H x D)	Unit	Without Stand: 12.3" x 7.6" x 6.7" With Stand: 12.5" x 7.8" x 8.6"
Weight	Unit	9.1 lbs. with stand
System Requirements	PC	IBM PC/AT or compatible PC CD-ROM Drive Pentium III 1 GHz or higher USB 2.0 Interface Windows 2000 or XP 256 MB RAM Minimum 200 MB free space (except for data file)